

# XP8 Liner Selector Chart

Liners Selector Chart							XP8-200A	XP8-300A	XP8-350A	XP8-400A	XP8-320W	XP8-450W
Stock Code	Description	Length	Wire Size	Application	Model							
<b>A</b> XP2024-09-30	Steel Liner	3mt / 10 ft	.023"-.035" / 0.6-0.9mm	Steel Wires		■	■	□	□	□	□	
XP2024-09-40	Steel Liner	4mt / 13 ft	.023"-.035" / 0.6-0.9mm	Steel Wires		■	■	□	□	□	□	
XP2024-09-50	Steel Liner	5mt / 16 ft	.023"-.035" / 0.6-0.9mm	Steel Wires		■	■	□	□	□	□	
<b>A</b> XP2024-12-30	Steel Liner	3mt / 10 ft	040"-.045" / 1.0-1.2mm	Steel Wires		■	■	□	□	■	□	
XP2024-12-40	Steel Liner	4mt / 13 ft	040"-.045" / 1.0-1.2mm	Steel Wires		■	■	□	□	■	□	
XP2024-12-50	Steel Liner	5mt / 16 ft	040"-.045" / 1.0-1.2mm	Steel Wires		■	■	□	□	■	□	
<b>A</b> XP2024-16-30	Steel Liner	3mt / 10 ft	.045"-.063" / 1.2-1.6mm	Steel Wires		□	□	□	□	■	□	
XP2024-16-40	Steel Liner	4mt / 13 ft	.045"-.063" / 1.2-1.6mm	Steel Wires		□	□	□	□	■	□	
XP2024-16-50	Steel Liner	5mt / 16 ft	.045"-.063" / 1.2-1.6mm	Steel Wires		□	□	□	□	■	□	
<b>B</b> XP2024PC-12-30	Polyamide-Copper Liner	3mt / 10 ft	.030"-.045" / 0.8-1.2mm	Soft Wires		■	■	■	□	■	■	
XP2024PC-12-40	Polyamide-Copper Liner	4mt / 13 ft	.030"-.045" / 0.8-1.2mm	Soft Wires		■	■	■	□	■	■	
XP2024PC-12-50	Polyamide-Copper Liner	5mt / 16 ft	.030"-.045" / 0.8-1.2mm	Soft Wires		■	■	■	□	■	■	
<b>B</b> XP2024PS-12-30	Polyamide-Steel Liner	3mt / 10 ft	.030"-.045" / 0.8-1.2mm	Hard Wires		■	■	■	□	■	■	
XP2024PS-12-40	Polyamide-Steel Liner	4mt / 13 ft	.030"-.045" / 0.8-1.2mm	Hard Wires		■	■	■	□	■	■	
XP2024PS-12-50	Polyamide-Steel Liner	5mt / 16 ft	.030"-.045" / 0.8-1.2mm	Hard Wires		■	■	■	□	■	■	
<b>A</b> XP3524-12-30	Steel Liner	3mt / 10 ft	040"-.045" / 1.0-1.2mm	Steel Wires				■	■	□	■	
XP3524-12-40	Steel Liner	4mt / 13 ft	040"-.045" / 1.0-1.2mm	Steel Wires				■	■	□	■	
XP3524-12-50	Steel Liner	5mt / 16 ft	040"-.045" / 1.0-1.2mm	Steel Wires				■	■	□	■	
<b>A</b> XP3524-16-30	Steel Liner	3mt / 10 ft	.045"-.063" / 1.2-1.6mm	Steel Wires				■	■	□	■	
XP3524-16-40	Steel Liner	4mt / 13 ft	.045"-.063" / 1.2-1.6mm	Steel Wires				■	■	□	■	
XP3524-16-50	Steel Liner	5mt / 16 ft	.045"-.063" / 1.2-1.6mm	Steel Wires				■	■	□	■	
<b>B</b> XP3524PC-16-30	Polyamide-Copper Liner	3mt / 10 ft	.045"-.063" / 1.2-1.6mm	Soft Wires				■	□	■	■	
XP3524PC-16-40	Polyamide-Copper Liner	4mt / 13 ft	.045"-.063" / 1.2-1.6mm	Soft Wires				■	□	■	■	
XP3524PC-16-50	Polyamide-Copper Liner	5mt / 16 ft	.045"-.063" / 1.2-1.6mm	Soft Wires				■	□	■	■	
<b>B</b> XP3524PS-16-30	Polyamide-Steel Liner	3mt / 10 ft	.045"-.063" / 1.2-1.6mm	Hard Wires				■	□	■	■	
XP3524PS-16-40	Polyamide-Steel Liner	4mt / 13 ft	.045"-.063" / 1.2-1.6mm	Hard Wires				■	□	■	■	
XP3524PS-16-50	Polyamide-Steel Liner	5mt / 16 ft	.045"-.063" / 1.2-1.6mm	Hard Wires				■	□	■	■	
<b>A</b> XP4024-24-30	Steel Liner	3mt / 10 ft	.080"-.095" / 2.0-2.4mm	Steel Wires				□	■	□	■	
XP4024-24-40	Steel Liner	4mt / 13 ft	.080"-.095" / 2.0-2.4mm	Steel Wires				□	■	□	■	
XP4024-24-50	Steel Liner	5mt / 16 ft	.080"-.095" / 2.0-2.4mm	Steel Wires				□	■	□	■	
<b>B</b> XP4024PC-20-30	Polyamide-Copper Liner	3mt / 10 ft	.063/.080" / 1.6-2.0mm	Soft Wires				□	■	□	■	
XP4024PC-20-40	Polyamide-Copper Liner	4mt / 13 ft	.063/.080" / 1.6-2.0mm	Soft Wires				□	■	□	■	
XP4024PC-20-50	Polyamide-Copper Liner	5mt / 16 ft	.063/.080" / 1.6-2.0mm	Soft Wires				□	■	□	■	
<b>B</b> XP4024PS-20-30	Polyamide-Steel Liner	3mt / 10 ft	.063/.080" / 1.6-2.0mm	Hard Wires				□	■	□	■	
XP4024PS-20-40	Polyamide-Steel Liner	4mt / 13 ft	.063/.080" / 1.6-2.0mm	Hard Wires				□	■	□	■	
XP4024PS-20-50	Polyamide-Steel Liner	5mt / 16 ft	.063/.080" / 1.6-2.0mm	Hard Wires				□	■	□	■	

■ Solid Box = Recommended Liner □ Clear Box = Compatible Liner

