



This Cover Lens satisfies the essential requirements of European Directive 89/686/EEC and standard EN 166 (2001): "Personal eye-protection"

**MODEL**

XR520

**STORAGE**

Keep the product in its original package. Do not put any weight above it. Keep it in a dry, fresh and ventilated area, sheltered from sunlight and away from chemical and abrasive substances.

**MAINTENANCE**

To clean, rinse with water at room temperature (20°C ±5°C) with mild detergent. Do not use hot water or dissolvent. Dry with a soft cloth. Never use abrasive cloth and do not dry close to a heat source. If required, a small amount of disinfectant in line with manufacturers' instruction can be added to the cleaning solution.

**DEADLINE OF OBSOLESCENCE**

Service life is basically depending on the care supplied and conditions of use. Under normal circumstances the eye protector should offer adequate protection for up to 6 months

**FIELD OF USE AND PERFORMANCE**

This safety cover lens has been issued for your personal safety. It must be fitted to the Parweld XR915H helmet when the helmet is in use. Ensure you understand when it should be fitted at all times and if there are any queries you should ask your supervisor. This lens is suitable for basic use and low energy impact. The CE marking indicates that it is manufactured according to the European Standard for the basic use only. It may be suitable for other uses and it will be further marked with a letter or number to indicate these uses as follows. The eye protector is suitable for use in accordance with the marking of the lenses and frame.

**PACKAGING SUITABLE FOR TRANSPORT**

Cover lens shall keep in the original packing with 10pcs per pack these should be protected by a further outer carton or padded envelope for transport.

**INSTALLATION**

Remove the protective film from the rear of the cover lens and insert one side of the lens under the lugs in the XR915H helmet, flex the cover lens so that the other side can be inserted under the lugs on the opposite side of the helmet shell. Remove the protective film from the front of the lens and ensure the lens is seated in the helmet and there are no gaps between the helmet and the cover lens.

**MARKING**

The marking of cover Lens contain the relevant technical information presented as follows:

Identification of the manufacturer..... Parweld

Optical class .....1

**IDENTIFICATION SYMBOLS FOR MECHANICAL STRENGTH**

Symbol	Mechanical strength requirements
No symbol	Minimum robustness
S	Increased robustness
F	Low energy impact
B	Medium energy impact
A	High energy impact

When more than one of these figures is shown, then the safety eyewear is suitable for a combination of uses for any one of those shown.

**CAUTION**

The above safety cover lens is impact resistant but not unbreakable. Clean and inspect regularly. Pitted or scratched lenses reduce vision and seriously reduce protection - replace immediately. If in doubt consult your safety supervisor or the manufacturer.

**WARNING**

If protection against high speed particles at extremes of temperature is required then the selected eye-protector should be marked with the letter T immediately after the impact letter, i.e. FT

If the impact letter is not followed by the letter T then the eye protector shall only be used against high speed particles at room temperature.

**NAME AND ADDRESS OF NOTIFIED BODIE**

Din Certco  
Gartenstrasse 133  
73430  
Aalen  
Germany  
NOTIFIED BODY: 0196

**MANUFACTUER**

Parweld Ltd  
Long Bank,  
Bewdley  
Worcs  
UK  
DY12 2TZ