



PRO-GRIP MAX[®] 150A FLEX

AIR COOLED MIG TORCH

180A CO₂, 150A Mixed Gas @ 60% Duty Cycle, EN60974-7, 0.6mm-1.0mm (.023"-0.040") Wires




STOCK CODE	DESCRIPTION
PRO1500FX-30ER	Flex Torch c/w Euro Fitting x 3m
PRO1500FX-40ER	Flex Torch c/w Euro Fitting x 4m

STOCK CODE	DESCRIPTION
1 B1501FX	Swan Neck
2 B1518	Gun Plug Housing c/w Nut
3 B1519PL	Gun Plug Nut-Plastic c/w Insert


C Liners See page 114 for full range	
STOCK CODE	DESCRIPTION
B1535-30*	Steel 0.6-0.9mm (.023-.035") x 3m
B1535-40*	Steel 0.6-0.9mm (.023-.035") x 4m
B1535-50*	Steel 0.6-0.9mm (.023-.035") x 5m
B1536-30	Teflon 0.6-0.9mm (.023-.035") x 3m

FULL PARTS BREAKDOWN AVAILABLE
visit www.parweld.com for more information.


ALTERNATIVE ENDS AVAILABLE
See pages 164 - 165 for more information.

Nozzles



STOCK CODE	STYLE	BORE
B1529	Cylindrical	16mm (5/8")
B1530*	Conical	12mm (15/32")
B1531	Tapered	11mm (7/16")



B1532	Bottle	13mm (1/2")
-------	--------	-------------



B1533	Spot	16mm (5/8")
-------	------	-------------

Contact Tips


STOCK CODE	WIRE SIZE	MATERIAL
B1527-06	0.6mm (.023")	ECu
B1527-08*	0.8mm (.030")	ECu
B1527-09	0.9mm (.035")	ECu
B1527-10	1.0mm (.040")	ECu

ROLL MARKING

All Parweld consumables are roll marked to enable you to identify genuine Parweld product.

* Denotes standard build